

Package: pakete (via r-universe)

September 18, 2026

Type Package

Title Utilities for Package Development

Version 0.2.1.9000

Description Tools and utilities for package development currently not available from usual development tools. These are mostly linked to personal preferences during the development process. They assist in making routine and repetitive tasks easily implementable.

License GPL (>= 3)

Depends R (>= 4.2.0)

Imports cli, jsonlite, utils, withr

Suggests knitr, rmarkdown, spelling, testthat (>= 3.0.0)

Encoding UTF-8

Language en-GB

LazyData true

RoxygenNote 7.3.3

Roxygen list(markdown = TRUE)

URL <https://katilingban.io/pakete/>,
<https://github.com/katilingban/pakete>

VignetteBuilder knitr

Config/testthat/edition 3

Repository <https://katilingban.r-universe.dev>

Date/Publication 2026-01-30 11:30:29 UTC

RemoteUrl <https://github.com/katilingban/pakete>

RemoteRef HEAD

RemoteSha a52089eefc39a8b149c33bf70dd41aa391593060

Contents

add_badge_status 2

add_contributing 3

add_github_action 3

add_issue_template 4

add_logo 5

Index 6

add_badge_status	Add badges to README
------------------	----------------------

Description

Add badges to README

Usage

```
add_badge_status(  
    status = c("concept", "wip", "suspended", "abandoned", "active", "inactive",  
              "unsupported", "moved"),  
    path = NULL,  
    .url = NULL  
)  
  
add_badge_codefactor(repo = NULL, path = NULL)  
  
add_badge_zenodo(repo = NULL, path = NULL)
```

Arguments

status	A character value for status to be assigned to project. This can be either " <i>concept</i> ", " <i>wip</i> ", " <i>suspended</i> ", " <i>abandoned</i> ", " <i>active</i> ", " <i>inactive</i> ", " <i>unsupported</i> ", or " <i>moved</i> ".
path	Path to file to add repostatus badge to. Set to NULL by default which would indicate that a README file in the root directory of the project is the target file.
.url	If status is "moved", the URL to which the repository has moved to. Otherwise NULL.
repo	Short remote git repository name. If NULL, is determined based on current git settings.

Value

An entry to the badge section of the README of the repository. Otherwise, a print of the markdown text for the status badge.

Examples

```
if (FALSE) {  
  add_badge_status("wip")  
  add_badge_codefactor(repo = "katilingban/pakete")  
  add_badge_zenodo(repo = "katilingban/pakete")  
}
```

add_contributing	<i>Add contributing markdown</i>
------------------	----------------------------------

Description

Add contributing markdown

Usage

```
add_contributing(repo = NULL, overwrite = FALSE)
```

Arguments

repo	Short remote git repository name. If NULL, is determined based on current git settings.
overwrite	Logical. Should an existing CONTRIBUTING.md file be overwritten? Default to FALSE.

Value

A CONTRIBUTING.md file in the .github directory

Examples

```
if (FALSE) add_contributing("katilingban/pakete")
```

add_github_action	<i>Add GitHub Actions</i>
-------------------	---------------------------

Description

Add GitHub Actions

Usage

```
add_github_action(gha_name = NULL, repo = NULL, overwrite = FALSE)
```

Arguments

gha_name	Short name of GitHub Action to add. Currently supports GitHub Action for Netlify deployment of testing version of pkgdown website (" <i>netlify</i> "), GitHub Action for mirroring to Codeberg (" <i>mirror-codeberg</i> "), and GitHub Action for R-universe testing (" <i>r-universe-test</i> ").
repo	Short remote git repository name. If NULL, is determined based on current git settings. Evaluated only if gha_name is " <i>mirror-codeberg</i> ".
overwrite	Logical. Should an existing GitHub Action be overwritten? Default is FALSE.

Value

A GitHub Action YAML file of the specified workflow to be added in `.github/workflows` directory.

Examples

```
if (FALSE) add_github_action(gha_name = "netlify")
```

add_issue_template	<i>Add issue templates</i>
--------------------	----------------------------

Description

Add issue templates

Usage

```
add_issue_template(
  issue = NULL,
  path = ".github/ISSUE_TEMPLATE",
  overwrite = FALSE
)
```

Arguments

issue	A character value of type of issue template to create. Choices are " <i>initial-cran-release</i> ", " <i>update-cran-release</i> ", " <i>submission-cran</i> ", and " <i>acceptance-cran</i> ".
path	Path to file to add issue template into. Set to <code>".github/ISSUE_TEMPLATE"</code> which is the default location specified by GitHub.
overwrite	Logical. If an existing issue template with the same file name is found, should it be overwritten? Default to FALSE.

Value

A specified issue template markdown file in the specified path.

Examples

```
if (interactive()) add_issue_template("initial-cran-release")
```

`add_logo`*Add HTML snippet for package hex sticker in README*

Description

Add HTML snippet for package hex sticker in README

Usage

```
add_logo(repo = NULL)
```

Arguments

repo	Short remote git repository name. If NULL, is determined based on current git settings.
------	---

Value

An entry to the first level header section of the README of the repository.

Examples

```
if (interactive()) add_logo()
```

Index

add_badge_codefactor
 (add_badge_status), [2](#)
add_badge_status, [2](#)
add_badge_zenodo (add_badge_status), [2](#)
add_contributing, [3](#)
add_github_action, [3](#)
add_issue_template, [4](#)
add_logo, [5](#)